












Wenzhou Jiahao Petroleum Machinery Co.,Ltd

ADD: Dong'ou Industrial District, Oubei Town, Wenzhou City, Zhejiang, China Tel:86-15869660419

ADBLUE SERIES

ITEM	PRODUCT	PICTURE	SPECIFICATION		UNIT PRICE
1	JH-F15 Stainless Steel Auto nozzle		Stainless Steel	Oil inlet:BSP3/4" diametereo of Spout:13/16" Flow rate:20-60L/min Color of cover:blue/yellow	
	Stainless Steel adblue nozzle accessories				
	Auto nozzle with teflon body		TEFLON	Oil inlet:BSP3/4" diametereo of Spout:13/16" Flow rate:20-60L/min Color of cover:blue/yellow	
	JH-F14 Auto Plastic Nozzle		Plastic	Oil inlet:BSP3/4" diametereo of Spout:13/16" Flow rate:20-60L/min Color of cover:blue/yellow	
	plastic adblue nozzle accessories				
2	swivel		Stainless Steel		
3	JH-F15 Stainless Steel Auto nozzle with magnet spout		Stainless Steel	Oil inlet:BSP3/4" diametereo of Spout:13/16" Flow rate:20-60L/min Color of cover:blue/yellow	
	Auto nozzle with teflon body		TEFLON		
	JH-F14 Auto Plastic Nozzle		Plastic		
4	Adblue Automatic Nozzle		Inlet Thread:BSP3/4" Flow rate:30L/min(big size) 15L/min(small size) Working pressure:0.18-0.5Mpa Temperature:-20℃ - 40℃		
5	Adblue Automatic Nozzle with meter		Inlet Thread:BSP3/4" Flow rate:30L/min(big size) 15L/min(small size) Working pressure:0.18-0.5Mpa Temperature:-20℃ - 40℃		

6	JH-F02 PLASTIC MANUAL ADBLE NOZZLE		INLET: 3/4"	
7	JH-F01 PLASTIC MANUAL ADBLE NOZZLE WITH STAINLESS STEEL SPOUT		INLET: 3/4"	
8	JH-T14 AC ADBLUE PUMP		Inlet/Outlet:1" Voltage:DC 12V Self priming:2.8Bar Flow rate:40L/min Max.Suction head:Dry 5	
9	JH-15 DC Urea Pump		Inlet/Outlet:1" Voltage:DC 12V Self priming:2.8Bar Flow rate:35L/min Max.Suction head:Dry 5	
10	JH-M01 Turbine Type Flowmeter		Inlet/Outlet:BSP 1" Flow rate:20-120L/min Accuarcyct:±1% Max.pressure:20Bar Repeatability:≤0.2% Display:Digital LCD	
11	JH-M02 Turbine Type Flowmeter		Inlet/Outlet:BSP 1" Flow rate:20-120L/min Accuarcyct:±1% Max.pressure:20Bar Repeatability:≤0.2% Display:Digital LCD	
12	swivel		Stainless Steel	
13	DJ Flowmeter			
14	JH-JF65 adblue flow meter		Stainless Steel	Flow rate:5-65L/min Accuarcyct:±0.2% Repeatability:≤0.07%
			TEFLON	Displacement per revolution: 0.5L min adjustable: 0.05%
15	OGM stainless steel flowmeter		Inlet&outlet: 1" flow rate: 5-100L/min voltage: DC 3~10V CURRENT: 10UA Accuracy: ±0.05% max speed: 2000R/min pluse: 0.0156L/pluse	
16	stainless steel swivel		3/4"	

17	stainless steel breakway			
18	stainless steel sight glass		3/4"	
19	swivel stainless steel		3/4"	
20	Swivel stainless steel		3/4"	
21	dual flowrate solenoid valve		Diameter: Dn20 Rated power: 2x5.5w Rated pressure: AC220V, DC12V/14V RATED FLOWRATE: >40L/min (big rate) 3-5L/min (small rate)	













Wenzhou Jiahao Petroleum Machinery Co.,Ltd

ADD: Dong'ou Industrial District, Oubei Town, Wenzhou City, Zhejiang, China Tel:86-15869660419

VAPOR RECOVERY PRODUCTS

ITEM	PRODUCT	PICTURE	SPECIFICATION		UNIT PRICE
1	JH-VRQ-80 Vapor Recovery Nozzle		Temperature:-20℃ to + 40℃ Max Flow Rate:45L/M Working pressure:1.5 to 3.5 bar Inlet Thread:M34*1.5 Weight:1.2KG		
	JH-VRQ-80 Vapor Recovery accessories				
2	JH-VRQ-70 Vapor Recovery Nozzle		Temperature:-20℃ to + 40℃ Max Flow Rate:38L/M Working pressure:0.22 to 0.35 Mpa Inlet Thread:M34*1.5 Weight:1.6KG		
	JH-VRQ-70 Vapor Recovery accessories				
3	JH-VRP-70 Vapor Recovery Vacuum Pump		Voltage:220V	Ex-Mark:Exd II AT3 Gb Protection Level:IP54 Voltage:220V/380V Power:370W Current:3/1 Flow Rate:60L/min Speed:2800RPM Max.Vacuum:0.04Mpa Vapor Hose Thread:1/2" Weight:12.8KG	
			Voltage: 380V		
	JH-VRP-70 Vapor Recovery Vacuum Pump(single)		Voltage:220V		
		Voltage: 380V			
JH-VRP-70 Vapor Recovery Vacuum Pump (Double)		Voltage:220V			
		Voltage: 380V			
4	JH-VRP-60 Vapor Recovery Vacuum Pump		Ex-Mark:Exd II AT3 Gb Protection Level:IP55 Voltage:36VDC Power:45W Current:2A Flow Rate:80L/min Speed:1500RPM Max.Vacuum:0.04Mpa Vapor Hose Thread: 1/2"		

5	JH-VYB-110 Vapor Recovery Pump		<p>Voltage:220V</p> <p>Voltage: 380V</p>	<p>Ex-mark:Ex d IIB T3 Gb IP Grade:IP55 Temperature:-40℃~+60℃ Pressure:100 kPa Max Flow Rate:110L/min Setting vacuum:22~26 kPa Current: 1.6A 0.44A motor power:120W working system:S1 noise: <65 dB (A) Weight:10.5 Kg inlet/outlet:1/2"</p>	
6	Vapor Recovery Hose Assembly		4.5M 彩色加5元一米		
7	SHORT HOSE SPARE PART				
8	JH-OGMS-300 vapor recovery monitoring vontroler			<p>1)Powersupply:AC220±10%、50±1Hz 2)Communication Method:RS-485 Bus 3)Explosion-proof Mark: Ex d mb IIBT4 Gb(system) 4)Monitor(12.1inch capacitive touch one machine) Display: 12.1"LED,resolution 1024*768; Touch screen: industrialtouch screen; Interface: 4 USB ports,2 serial ports,2 Ethernetports 5)Installation location:safety area such as gas station shop</p>	
9	JH-OGMS-300-1 gas-liquid ratio acquisition controller			<p>1)Power supply:24VDC±10% 2)Communication Method:RS-485 Bus 3)Explosion-proof Mark: Ex d mb IIBT4 Gb(system) 4)Qty:1PC/2nozzles(on the same fuel dispenser) 5)Installation location: installed in the computer box of fuel dispenser</p>	
10	JH-LLQZ-15W gas roots flow meter			<p>1)Power Supply:DC5~24V 2)Communication Method:Pulse signal or 485 communication signal 3)Accuracy Level:±1.5% 4)Explosion-proof Mark: Exd IBT4 Gb 5)ConnectingThread :BSPT1/2</p>	
11	CH/QYF 24 VDC electronic gas-liquid ratio regulating valve			<p>1)Power Supply: 24VDC ±10% 2)Connecting Thread: G1/4 3)Control way:Duty cycle 4)Explosion-proof Mark: Ex mb IICT3 Gb 5)Qty:1pc/nozzle 6)Installation location:Installed on thenegative pressure side of thevaporrecovery pump in the fueldispenser .</p>	
12	MPM489 pressure transmitter			<p>1)Power Supply:DC11-28V 2)Communication Method: 4~20mA 3)Measure:-3kPa~+3kPa 4)Explosion-proof Mark: Ex dIICT6 Gb 5)Connecting Thread:M20×1.5</p>	
13	YT-95H combustible gas concentration sensor (catalytic principle)			<p>1)Power Supply: 24VDC ±10% 2)Communication Method: 4~20mA/RS485 3)Connecting Thread:M45X2 4)Explosion-proof Mark: Ex dIICT6 Gb</p>	
14	vapor recovery detector				










15	JH-TL20 Stage III Vapor recovery processing device		<p>FLOW RATE: 3m³ /h~6m³ /h REFRIGERANT: R404a VOLTAGE: AC380V / 50Hz EXPLOSION-PROOF CE NO.: CE20.5034X EXHAUST EMISSION CONCENTRATION: NMHC ≤25g/m³ MAX WORK PRESSURE: 2.5MPa EXPLOSION-PROOF MARK: Ex d e ia mb px IIB T4 Gb WORKING TEMP: -25℃~55℃ OUT SIZE:1250x1130x1480 (mm)</p>	
15	vapor recovery visible filter			
16	Vapor Recovery Breakaway		M34*1.5	
17	Vapor Recovery Breakaway		M34*1.5	
18	vapor recovery proportional valve		M34*1.5	
19	vapor recovery adaptor		M34*1.5 material: aluminum alloy	
20	vapor recovery sight glass		M34*1.5 female 3/4" male material: aluminum alloy	
21	COVER		OPW: 75*55mm ZVA:92*75mm	
22	JH-VRQ-80 COVER			
23	JH-VRQ-70 Vapor COVER			












Wenzhou Jiahao Petroleum Machinery Co.,Ltd

ADD: Dong'ou Industrial District, Oubei Town, Wenzhou City, Zhejiang, China Tel:86-15869660419

FUEL NOZZLES

ITEM	PRODUCT	PICTURE	SPECIFICATION	UNIT PRICE
1	JH-11A Automatic Nozzle		Oil inlet:BSP3/4" diametero of Spout:13/16" or 15/16" Flow rate:0-45L/min or 0-60L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
2	JH-11AP Automatic Nozzle		Oil inlet:BSP3/4" diametero of Spout:13/16" or 15/16" Flow rate:0-45L/min or 0-60L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
3	JH-11B Automatic Nozzle		Oil inlet:BSP3/4" diametero of Spout:13/16" or 15/16" Flow rate:0-45L/min or 0-60L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
	11A Accessories			
4	JH-120L Automtaic nozzle big spout		Oil inlet: BSPT1" Diameter of Spout : big spout Flowrate : 0-120L/min Material:aluminum Color ofinsulator : red/green/blue/yellow/black	
	120 Accessories			
5	JH-120L Automtaic nozzle small spout		Oil inlet: BSPT1" Diameter of Spout : small spout Flowrate : 0-60L/min Material:aluminum Color ofinsulator : red/green/blue/yellow/black	
6	JH-F05 ZVA-1 Auto Shutoff Nozzle		Inlet Thread:BSP3/4" diametero of Spout:20mm Flow rate:0-45L/min or 0-60L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
	JH-F05 ZVA-1 accessories			

7	JH-F05 ZVA-2 Auto Shutoff Nozzle		Oil inlet:BSP3/4" diameters of Spout:13/16" or 15/16" Flow rate:0-45L/min or 0-60L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
	JH-F05 ZVA-2 accessories			
8	JH-F06 ZVA-2 Auto Shutoff Nozzle		Oil inlet:BSP/NPT1" diameters of Spout:1/1/16 Flow rate:0-120L/min Material:aluminum Color of cover:red/green/blue/yellow/black	
9	JH-12A Manual Nozzle		Oil inlet:BSP3/4",1" Flow rate:0-45L/min or 0-60L/min Material:aluminum	
10	JH-13A Manual Nozzle		Oil inlet:BSP3/4",1" Flow rate:0-45L/min or 0-60L/min Material:aluminum	
11	JH-F16 1290 Auto Shutoff Nozzle		Oil inlet:BSP1.5" Nominal Pressure:3Mpa Material:aluminum Shape:Membrane Valve	
12	JH-F17 Automatic Nozzle With Meter		Oil inlet:BSP3/4" Flow rate:20-60L/min Material:all Plastic	
13	JH-F10 Manual Nozzle With Meter		Oil inlet:BSP3/4" Flow rate:20-60L/min Material:all Plastic	
14	new Automatic Nozzle With Meter			
15	11A COVER			
16	120 Vapor COVER			














Wenzhou Jiahao Petroleum Machinery Co.,Ltd

ADD: Dong'ou Industrial District, Oubei Town, Wenzhou City, Zhejiang, China Tel:86-15869660419

FUEL PUMP & FLOW METER

ITEM	PRODUCT	PICTURE	SPECIFICATION		UNIT PRICE
1	DYB40-DC12 Diesel pump		Flow Rate:20L-60L/min Max. Pressure:3 Bar Power:DC12 By pass Valve:Yes Strainer:yes Inlet&outlet:3/4" Power:120W		
2	DYB60-AC220 Diesel pump		Flow Rate:20L-60L/min Max. Pressure:3 Bar Power:AC220V By pass Valve:Yes Strainer:Yes Inlet&outlet:1" Power:550W		
3	DYB80-AC220 Diesel pump		Flow Rate:20L-80L/min Max. Pressure:3 Bar Power:AC220V By pass Valve:Yes Strainer:Yes Inlet&outlet:1" Power:750W		
4	JH-M05 Mecanical Flow meter		size:1"	Inlet/Outlet:BSP 1",1.5",2" Measurement :Litre/US Gallon Accuarcyct:±1% Max.pressure:3Bar Flow rate:40GPM	
			size:1.5"		
			size:2"		
5	JH-M06 Electornic Oval Gear Flow meter		Inlet/Outlet:BSP 1/2",3/4" Measurement :Litre/US Gallon Accuarcyct:±0.5% Max.pressure:70Bar Flow rate:10-30L/min Repeatability:≤0.2%		
6	JH-M10 Mecanical Flow meter		Inlet/Outlet:BSP 1" Measurement :Litre Accuarcyct:±1% Max.pressure:3Bar Flow rate:20-120L/Min		
7	TEM-25 Digital Turbine Oil Flow Meter		Inlet Size: 1" Flow Rate: 20-150lpm	Body material:Aluminum Accuarcyct:±0.5%Max Max.pressure:20Bar Application Medium:Diesel, Petrol,light oil	
	TEM-40 Digital Turbine Oil Flow Meter		Inlet Size: 1.5" Flow Rate: 40-350lpm		
8	OGM-50 Oval Gear Meter		Size:2" Flow rate: 60-300L/min	Accuarcyct:±0.2% or 0.5% Repeatability:≤0.03% Max. Viscosity:1000CPS Max.pressure:1.8Mpa	
	OGM-80 Oval Gear Meter		Size:3" Flow rate: 140-700L/min		
	OGM-E-25 Electronic Oval Gear Meter		Size:1" Flow rate: 20-120L/min Max.pressure: 3.4Mpa		

9	OGM-E-40 Electronic Oval Gear Meter		Size:1.5" Flow rate: 25- 250L/min Max.pressure: 1.8Mpa	Accuarcyct:±0.5% Repeatability:≤0.03% Max. Viscosity:1000CPS	
	OGM-E-50 Electronic Oval Gear Meter		Size:2" Flow rate: 30- 300L/min Max.pressure: 1.8Mpa		
10	OGM-A-25 Machinery Oval Gear Meter		Size:1" Flow rate: 20- 120L/min Max.pressure: 3.4Mpa	Accuarcyct:±0.5% Repeatability:≤0.03% Max. Viscosity:1000CPS	
	OGM-A-40 Machinery Oval Gear Meter		Size:1.5" Flow rate: 25- 250L/min Max.pressure: 1.8Mpa		
	OGM-A-50 Machinery Oval Gear Meter		Size:2" Flow rate: 30- 300L/min Max.pressure: 1.8Mpa		
11	ETP-40A		Nodel:ETP-40A Pump:DYB-40 Flow meter:FM-120L Hose:4M Manual nozzle:J60-4 Bracket:Yes Inlet Hose:2M		
12	ETP-60A		Nodel:ETP-60A Pump:DYB-60 Flow meter:FM-120L Hose:4M Manual nozzle:J60-4 Bracket:Yes Inlet Hose:2M		
13	ETP-80A		Nodel:ETP-80A Pump:DYB-80 Flow meter:FM-120L Hose:4M Manual nozzle:J60-4 Bracket:Yes Inlet Hose:2M		
14	TSC-40 FLOW METER		Size: 40mm 1.5" Flowrate:25-250 Vol/R: 0.309L	Max Pressure: 10 Bar/150psi Accuracy: ±0.2% Repeatability:≤0.03% Unit: Liter/Gallon	
	TSC-50 FLOW METER		Size: 50mm 2" Flowrate:28-380 Vol/R: 0.681L		
	TSC-80 FLOW METER		Size: 80mm 3" Flowrate:75-750 Vol/R: 1.839L		
	TSC-100B FLOW METER		Size: 100mm 4" Flowrate:17-1700 Vol/R: 5.102L		
15	QYB -240 Submersible turbine pump		Voltage: 220V, 50Hz Dimension: 380x310x380mm	Rating Pressure: 0.1MPa Max Flow Rate: 240L/min Rotate Speed:2820RPM Current:9A Power:1.1Kw Ex-proof Class: 1Px6.	
			Voltage: 380V,50Hz Dimension: 810x210x210mm	Fixation Thread: BSPF/NPT4" Inlet:BSPF/NPT 1" Outlet: BSPF/NPT2" Net Weight: 55kg Gross Weight:58kg Package:1PCS/2CTN	

16	JH-JL65 FLOW METER	 JH-JL65	Maximum flow:65L/min; Minimum flow: 5L/min	Displacement per revolution: 0.5l Accuracy error: ±0.2%; Repeatability error: ≤0.07%; Minimum adjustment amount: 0.05%;	
17	JH-JL85 FLOW METER	 JH-JL85	Maximum flow:85L/min; Minimum flow: 5L/min		
18	RSJ-50 Flow Meter				
19	ZYB-80/50 Transfer Pump		Speed: 630rpm Flow rate: 45~65l/min Vacuum: ≥0.054mpa Noise: ≤72db Working pressure: 1.6~2bar Dimension: 350×280×380mm Net weight: 15kg Gross weight : 16kg Package: 1pcs/ctn		
20	brass solenoid valve		3/4		
			1		









Wenzhou Jiahao Petroleum Machinery Co.,Ltd

ADD: Dong'ou Industrial District, Oubei Town, Wenzhou City, Zhejiang, China Tel:86-15869660419

ACCESSORIES

ITEM	PRODUCT	PICTURE	SPECIFICATION	UNIT PRICE
1	JH-2A Swivel 呆接		3/4"	
			1"	
2	JH-2B Swivel 活接		3/4"	
			1"	
3	JH-45 Swivel		3/4"	
			1"	
4	JH-45A Swivel		3/4"	
			1"	
5	JH-45B Swivel		3/4"	
			1"	
6	JH-1 Breakaway		1"	
7	JH-2 Breakaway		3/4"	
			1"	
8	JH-3 Breakaway		3/4"	
			1"	
9	36s Swivel		3/4"	
			1"	

10	NS-2 Nozzle Swivels		1"	
11	M19-1 Swivel		1"	
12	V19-1 Swivel		1"	
13	angel check valve		1.5"	
			2"	
14	Shut-off Valve			
15	Plastic Nozzle Holder			
16	Aluminum Nozzle Holder			
17	GL-1		1"	
	GL-2			
18	Foot valve		1"	
			1.5"	
			2"	

19	JH-PHQ Hose retractor for fuel dispenser		Tension standard is 50n-55n. Length: 2.7m Service life > 100,000 times	
20	LPG GAS NOZZLE		Temperature: -40~85°C Inlet: 3/4" 1"	
21	LT-1 STANDARD METAL PROVER		STIANLESS STEEL	
	LT-2 STANDARD METAL PROVER		CARBIN STEEL 5L	
			CARBIN STEEL 10L	
			CARBIN STEEL 20L	
			CARBIN STEEL 50	
CARBIN STEEL 100L				
CARBIN STEEL 200L				
LT-3 STANDARD METAL PROVER		STIANLESS STEEL 10L		
		STIANLESS STEEL 20L		
LT-4 STANDARD METAL PROVER		STIANLESS STEEL		